

TITLE

ELECTRON GUN FOR COLOR CATHODE RAY TUBE

CLAIM OF PRIORITY

[0001] This application makes reference to, incorporates the same herein, and claims all benefits accruing under 35 U.S.C. § 119 from an application for *ELECTRON GUN FOR COLOR CATHODE RAY TUBE* earlier filed in the Korean Industrial Property Office on 2 January 2001, and there duly assigned Serial No. 26/2001 by that Office.

BACKGROUND OF THE INVENTION

Technical Field

[0002] The present invention relates to an electron gun for a color cathode ray tube (CRT), and more particularly, to an electron gun for a color cathode ray tube in which the structure of an electrode for forming an asymmetrical beam forming lens is improved.

Related Art

[0003] An electron gun used in a large screen color cathode ray tube needs to be able to stably generate a low current electron beam and a high current electron beam. A cathode ray tube can adopt an in-line type electron gun and a deflection yoke of a self-converging type having a pincushion type deflection magnetic field and a barrel type deflection magnetic field. The deflection magnetic fields

1 of the deflection yoke vertically over-focuses and horizontally under-focuses the electron beam so
2 that a focus separation phenomenon occurs. The electron beam spot deformed as above becomes
3 asymmetrical when being deflected toward the periphery of a screen. Also, in the in-line type
4 electron gun, focus is not uniform due to a change in intensity of an electron lens generated by a
5 change in a focus voltage.

6 [0004] To prevent the above deterioration of the focus of an electron beam landing on a
7 fluorescent film, a method can be suggested in which distortion due to the irregular magnetic field
8 of a deflection yoke is compensated for by forming the profile of an electron beam emitted from the
9 electron gun to be vertically elongated.

10 [0005] U.S. Patent No. 5,128,586, issued to Ashizaki *et al.*, entitled *COLOR CATHODE RAY*
11 *TUBE GUN HAVING CONTROL GRID OF VARYING THICKNESS*, discloses an electron gun
12 emitting an electron beam having the vertically elongated profile which lands on the periphery of
13 a screen to compensate for distortion of the electron beam due to the irregular magnetic field of a
14 deflection yoke.

15 [0006] In an electron gun disclosed in U.S. Patent 5,128,586, an electron beam passing hole is
16 formed by penetrating an indented portion having a horizontally elongated shape at the side to which
17 an electron beam is input and an indented portion having a vertically elongated shape at the side

1 from which the electron beam is output. In the electron gun having the above control electrode,
2 distortion of the electron beam at the periphery of a screen is compensated for by moving the
3 position of a crossover point in the vertical direction than in the horizontal direction toward a screen.
4 However, since the diameter of a vertical electron beam passing through the rectangular electron
5 beam passing hole which is penetrated by the horizontally elongated and vertically elongated
6 indented portions is small, the control electrode interferes with a mask having a function of color
7 selection of the electron beam during scanning so that moiré of an image occurs.

8
9
10 [0007] U.S. Patent No. 5,760,550, issued to Sukeno *et al.*, entitled *COLOR PICTURE TUBE*,
discloses a color cathode ray tube having an electron gun in which an electron beam passing hole
of a control electrode is formed to be non-circular.

11
12 [0008] While U.S. Patent 5,128,586 and U.S. Patent No. 5,760,550 provide advantages, they
appear to fail to adequately provide an efficiently and conveniently improved electron gun.

13 SUMMARY OF THE INVENTION

14 [0009] To solve the above-described problems and others, it is an object of the present invention
15 to provide an electron gun for a color cathode ray tube (CRT) which makes the strength of an
16 electron lens different in the horizontal direction and the vertical direction at the triode portion, so
17 that defocusing by the deflection yoke is minimized, and moiré of the image is prevented.

1 **[0010]** To solve the above-described problems and others, it is a further object of the present
2 invention to provide an electron gun for a color cathode ray tube which makes the strength of an
3 electron lens different in the horizontal direction and the vertical direction at the triode portion, so
4 that the horizontal resolution of an image can be improved and a vertical focus property of the image
5 can be improved.

6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
22

1 [0013] Alternatively, to achieve the above objects and others, there is provided an electron gun
2 for a color cathode ray tube which comprises a cathode which is a source for emitting an electron
3 beam, a control electrode, through which the electron beam emitted from the cathode passes, having
4 first electron beam passing holes each including a first vertically elongated indented portion formed
5 at an output side surface of the control electrode and a first electron beam passing hole portion
6 formed in the first indented portion, a screen electrode installed adjacent to the control electrode and
7 having second electron beam passing holes formed in the screen electrode, a plurality of focusing
8 electrodes for forming a plurality of quadrupole lenses, sequentially installed from the screen
9 electrode and respectively having electron beam passing holes having a predetermined shape.

10 [0014] Alternatively, to achieve the above objects and others, there is provided an electron gun
11 for a color cathode ray tube which comprises a cathode which is a source for emitting an electron
12 beam, a control electrode, through which the electron beam emitted from the cathode passes, having
13 first electron beam passing holes each including a first vertically elongated indented portion formed
14 at an output side surface of the control electrode and a first electron beam passing hole portion
15 formed in the first indented portion, a screen electrode installed adjacent to the control electrode and
16 having second electron beam passing holes formed in the screen electrode, a plurality of first,
17 second, and third focusing electrodes respectively having electron beam passing holes having a
18 predetermined shape, a fourth focusing electrode installed adjacent to the third focusing electrode,

1 for forming a first quadrupole lens, a fifth focusing electrode installed adjacent to the fourth focusing
2 electrode, for forming a second quadrupole lens, and a final acceleration electrode installed adjacent
3 to the fifth focusing electrode, for forming a main lens.

4 [0015] It is preferred in the present invention that vertically elongated electron beam passing holes
5 are formed at an output side surface of each of the third and fourth focusing electrodes, horizontally
6 elongated electron beam passing holes are formed at an input side surface of each of the fourth and
7 fifth focusing electrodes, a constant voltage is applied to the screen electrode and the second
8 focusing electrode, a focusing voltage higher than the constant voltage is applied to the first focusing
9 electrode and the fourth focusing electrode, and a dynamic focusing voltage using the focusing
10 voltage as a base voltage is applied to the third and fifth focusing electrodes.

11 [0016] To achieve these and other objects in accordance with the principles of the present
12 invention, as embodied and broadly described, the present invention provides an electron gun for a
13 color cathode ray tube, the gun comprising: a cathode emitting an electron beam; a control electrode
14 having first hole regions, each one of the first hole regions including a first vertically elongated
15 indented portion formed at an output side surface of said control electrode and including a first hole
16 portion formed in the first indented portion, the electron beam passing through said control
17 electrode; a screen electrode being installed adjacent to said control electrode, said screen electrode
18 having second hole regions; and a plurality of focusing electrodes being sequentially installed from

1 said screen electrode.

2 **[0017]** To achieve these and other objects in accordance with the principles of the present
3 invention, as embodied and broadly described, the present invention provides an electron gun for a
4 color cathode ray tube, the gun comprising: a cathode emitting an electron beam; a control electrode
5 having first hole regions, each one of the first hole regions including a first vertically elongated
6 indented portion formed at an output side surface of said control electrode and including a first hole
7 portion formed in the first indented portion, the electron beam passing through said control
8 electrode; a screen electrode being installed adjacent to said control electrode, said screen electrode
9 having second hole regions; and a plurality of focusing electrodes forming a plurality of quadrupole
10 lenses, said focusing electrodes being sequentially installed from said screen electrode and
11 respectively forming electron beam passing holes having a predetermined shape.

12 **[0018]** To achieve these and other objects in accordance with the principles of the present
13 invention, as embodied and broadly described, the present invention provides a method, comprising:
14 passing an electron beam through first hole regions of a control electrode, each one of the first hole
15 regions including a first vertically elongated indented portion formed at an output side surface of said
16 control electrode and including a first hole portion formed in the first indented portion, the electron
17 beam passing through said control electrode; passing the electron beam through second hole regions
18 of a screen electrode; and passing the electron beam through a plurality of focusing electrodes

1 sequentially installed from said screen electrode.

2 **[0019]** To achieve these and other objects in accordance with the principles of the present
3 invention, as embodied and broadly described, the present invention provides a method, comprising:
4 passing an electron beam through first hole regions of a control electrode, each one of the first hole
5 regions including a first vertically elongated indented portion formed at an output side surface of said
6 control electrode and including a first hole portion formed in the first indented portion, the electron
7 beam passing through said control electrode; passing the electron beam through second hole regions
8 of a screen electrode; and passing the electron beam through a plurality of focusing electrodes that
9 form a plurality of quadrupole lenses, said focusing electrodes respectively forming electron beam
10 passing holes having a predetermined shape.

11 **[0020]** To achieve these and other objects in accordance with the principles of the present
12 invention, as embodied and broadly described, the present invention provides a computer storage
13 medium having stored thereon a set of instructions implementing a method, said set of instructions
14 comprising one or more instructions for: passing an electron beam through first hole regions of a
15 control electrode, each one of the first hole regions including a first vertically elongated indented
16 portion formed at an output side surface of said control electrode and including a first hole portion
17 formed in the first indented portion, the electron beam passing through said control electrode;
18 passing the electron beam through second hole regions of a screen electrode; and passing the electron

1 beam through a plurality of focusing electrodes that form a plurality of quadrupole lenses, said
2 focusing electrodes respectively forming electron beam passing holes having a predetermined shape.

3 [0021] The present invention is more specifically described in the following paragraphs by
4 reference to the drawings attached only by way of example. Other advantages and features will
5 become apparent from the following description and from the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] In the accompanying drawings, which are incorporated in and constitute a part of this specification, embodiments of the invention are illustrated, which, together with a general description of the invention given above, and the detailed description given below, serve to exemplify the principles of this invention.

[0023] FIG. 1 is an exploded perspective view showing an electron gun for a cathode ray tube;

12 [0024] FIG. 2 is an exploded perspective view showing another electron gun for a cathode ray
13 tube;

14 [0025] FIG. 3 is an exploded perspective view showing a first preferred embodiment of an
15 electron gun for a cathode ray tube, in accordance with the principles of the present invention;

16 [0026] FIG. 4 is an exploded perspective view showing a second preferred embodiment of an
17 electron gun for a cathode ray tube, in accordance with the principles of the present invention;

18 [0027] FIG. 5 is an exploded perspective view showing a third preferred embodiment of an

1 electron guns for a cathode ray tube, in accordance with the principles of the present invention; and
2 **[0028]** FIG. 6 is an exploded perspective view showing an electron gun for a cathode ray tube, in
3 which the application of voltages is shown, in accordance with the principles of the present
4 invention.

5 **DETAILED DESCRIPTION OF THE INVENTION**

6 **[0029]** While the present invention will be described more fully hereinafter with reference to the
7 accompanying drawings, in which preferred embodiments of the present invention are shown, it is
8 to be understood at the outset of the description which follows that persons of skill in the appropriate
9 arts may modify the invention here described while still achieving the favorable results of this
10 invention. Accordingly, the description which follows is to be understood as being a broad, teaching
11 disclosure directed to persons of skill in the appropriate arts, and not as limiting upon the present
12 invention.

13 **[0030]** Illustrative embodiments of the invention are described below. In the interest of clarity,
14 not all features of an actual implementation are described. In the following description, well-known
15 functions or constructions are not described in detail since they would obscure the invention in
16 unnecessary detail. It will be appreciated that in the development of any actual embodiment
17 numerous implementation-specific decisions must be made to achieve the developers' specific goals,
18 such as compliance with system-related and business-related constraints, which will vary from one

1 implementation to another. Moreover, it will be appreciated that such a development effort might
2 be complex and time-consuming, but would nevertheless be a routine undertaking for those of
3 ordinary skill having the benefit of this disclosure. Additionally, the features of the embodiments
4 disclosed can be combined to form an electron gun, in accordance with the principles of the present
5 invention.

6 **[0031]** The scope of this disclosure includes a computer storage medium having stored thereon
7 a set of instructions implementing a method in accordance with the principles of the present
8 invention. For example, the present invention provides a computer storage medium having stored
9 thereon a set of instructions implementing a method, said set of instructions comprising one or more
10 instructions for: passing an electron beam through first hole regions of a control electrode, each one
11 of the first hole regions including a first vertically elongated indented portion formed at an output
12 side surface of said control electrode and including a first hole portion formed in the first indented
13 portion, the electron beam passing through said control electrode; passing the electron beam through
14 second hole regions of a screen electrode; and passing the electron beam through a plurality of
15 focusing electrodes that form a plurality of quadrupole lenses, said focusing electrodes respectively
16 forming electron beam passing holes having a predetermined shape.

17 **[0032]** FIG. 1 is an exploded perspective view showing an electron gun for a cathode ray tube
18 (CRT). As shown in the drawing, an electron gun includes a cathode 11, a control electrode 12, and

a screen electrode 13 which form a triode portion, and focusing electrodes 14 forming a main lens and an auxiliary lens. Vertically elongated electron beam passing holes 12H are formed at the control electrode 13. Horizontally elongated electron beam passing holes 13H are formed the screen electrode 13 facing the control electrode 12. Circular electron beam passing holes 14H are formed at the focusing electrode 14 facing an output side surface of the screen electrode 13.

[0033] In the color cathode ray tube having the structure shown in FIG. 1, an incident angle of the main lens formed by the focusing electrode 14 is reduced by the vertically elongated electron beam passing holes 12H formed by the control electrode 11 and the horizontally elongated electron beam passing holes 13H formed by the screen electrode 12. Thus, dispersion of an image formed by an electron beam spot landing on the periphery of a screen due to the vertical deflection magnetic field of the deflection yoke is minimized and a uniform vertical focus is achieved.

[0034] Nevertheless, the above electron gun shows a limit to a very large or perfect flat screen surface. Also, a spot of an electron beam sensitively changes with respect to the amount of change in current according to the level of a video signal. Thus, as current increases, the diameter of a vertical beam of the electron beam increases drastically so that a focus property is deteriorated. Also, in the case of an electron gun, for a low current in which the density of current of the electron beam is lowered, the diameter of the electron beam decreases so that moiré occurs with respect to a low brightness.

1 [0035] FIG. 2 is an exploded perspective view showing another electron gun for a cathode ray
2 tube. Referring to the drawing, electron beam passing holes 22a and 24a of a control electrode 22
3 and a focusing electrode 24 are formed to be circular. Circular electron beam passing holes 23a are
4 formed at the screen electrode 23. A horizontally elongated indented portion 23b is formed at the
5 edge of each of the electron beam passing holes 23a at the output side surface of the screen electrode
6 23. In the above electron gun, a focusing force of a focusing region of a pre-focus lens formed
7 between the screen electrode 13 and the focusing lens 14 is weakened in the horizontal direction and
8 is strengthened in the vertical direction, so that resolution at the central portion and the periphery of
9 a screen is improved. Nevertheless, the adjustment of the crossover point of the electron beam is
10 not easy.

11 [0036] In a color cathode ray tube, an electron gun installed at a neck portion of a cathode ray tube
12 emits an electron beam to excite a fluorescent film. The electron gun includes a cathode, a control
13 electrode, and a screen electrode which form a triode portion, a plurality of focusing electrodes and
14 a final acceleration electrode for forming a main lens and an auxiliary lens.

15 [0037] FIG. 3 is an exploded perspective view showing a first preferred embodiment of an
16 electron gun for a cathode ray tube, in accordance with the principles of the present invention. FIG.
17 4 is an exploded perspective view showing a second preferred embodiment of an electron gun for
18 a cathode ray tube, in accordance with the principles of the present invention. FIG. 5 is an exploded

1 perspective view showing a third preferred embodiment of an electron guns for a cathode ray tube,
2 in accordance with the principles of the present invention.

3 **[0038]** A preferred embodiment of the triode portion for emitting an electron beam and forming
4 a point of an object in an electron gun is shown in FIG. 3. As shown in the drawing, a cathode 31
5 forming the triode portion includes an electron emission portion 31a where an electron emission
6 material is dipped or coated, and a heater 31b for heating the electron emission portion 31a. The
7 electron emission portion 31a can be supported by a base metal (not shown) which is supported by
8 a sleeve (not shown) installed inside and the electron emission portion 31a can be directly heated by
9 the heater 31b.

10 **[0039]** A first electron beam passing hole 100 is formed at a position corresponding to the cathode
11 31 at the control electrode 32 installed adjacent to the cathode 31. The first electron beam passing
12 hole 100 includes a vertically elongated first indented portion 101 formed at the output side surface
13 of the control electrode 32 and a first electron beam passing hole portion 102 formed in the first
14 indented portion 101. The first electron beam passing hole 100 can be referred to as a first hole
15 region 100.

16 **[0040]** Here, the first indented portion 101 can be formed to have a vertically elongated
17 rectangular or oval shape having a horizontal width W2 narrower than a vertical width W1. The first

electron beam passing hole portion 102 may be formed to have a circular shape, a rectangular shape as shown in FIG. 4, or a square shape as shown in FIG. 5 in which a vertical width W3 is the same as a horizontal width W4.

[0041] Preferably, the vertical width W3 of the first electron beam passing hole portion 102 is formed to be less than the vertical width W1 of the first indented portion 101. Also, the vertical width W4 of the first electron beam passing hole portion 102 is formed to be less than or the same as the horizontal width W2 of the first indented portion 101. According to the experiments by the present inventor, when the ratio of the vertical width W1 to the horizontal width W2 of the first indented portion 101 is set to be 1:1.2 to 1:1.7. The ratio of the vertical width W3 to the horizontal width W4 of the first electron beam passing hole portion 102 is set to be 1:2 to 1:1.5, the focus property is enhanced and generation of moiré is minimized.

[0042] In accordance with the principles of the present invention, the control electrode has at least one hole region 100, and the hole region 100 can be a vertically elongated oval shape or a vertically elongated rectangular shape. An indented portion 101 is part of the hole region 100. The indented portion 101 can be a vertically elongated oval shape or a vertically elongated rectangular shape. A hole 102 is part of the hole region 100. The hole 102 can be a circular shape, a vertically elongated oval shape, or a vertically elongated rectangular shape.

1 **[0043]** In accordance with the principles of the present invention, the control electrode has at least
2 one hole region 110, and the hole region 110 can be a circular shape, a vertically elongated oval
3 shape, or a vertically elongated rectangular shape. The hole region 110 can have no indented portion
4 (as shown in FIG. 3), or the hole region 110 can have an indented portion 111 (as shown in FIG. 5).
5 The indented region 111 can be a circular shape, a vertically elongated oval shape, or a vertically
6 elongated rectangular shape. A hole 112 is part of the hole region 110 shown in FIG. 5. The hole
7 112 can be a circular shape, a vertically elongated oval shape, or a vertically elongated rectangular
8 shape.

9 **[0044]** The screen electrode 33 has a plate shape and a second electron beam passing hole 110 is
10 formed to be coaxially with the corresponding cathode 31 and the first electron beam passing hole
11 portion 102. The second electron beam passing hole 110 can be formed to have a circular shape, as
12 shown in FIG. 3. The second electron beam passing hole 110 can be formed to have vertically
13 elongated rectangular shape like a second electron beam passing hole 110' in FIG. 4. As shown in
14 FIG. 5, the second electron beam passing hole 110 can be formed to include a second indented
15 portion 111 formed at the output side surface of the screen electrode 33 and a second electron beam
16 passing hole portion 112 formed in the second indented portion 111. The second electron beam
17 passing hole 110 can be referred to as a second hole region 110, as shown in FIG. 5.

18 **[0045]** The shape of the electron beam passing hole formed at the screen electrode 33 is not

1 limited to the above description and may be formed in various shapes to change the profile of the
2 electron beam. Electron beam passing holes for forming an electron lens and a quadrupole lens are
3 formed at the focusing electrodes other than a focusing electrode corresponding to the screen
4 electrode.

5 **[0046]** In the electron gun having the above structure, when the electron emission portion 31a is
6 heated by the heater 31b of the cathode 31, an electron beam is emitted from the cathode 31. The
7 electron beam is strongly focused in the horizontal direction and relatively weakly focused in the
8 vertical direction as it passes through a negative lens formed by the electron beam passing holes
9 between the control electrode 32 and the screen electrode 33. That is, since the vertically elongated
10 first indented portion 101 is formed at the output side surface of the control electrode 32 and the
11 circular or rectangular first electron beam passing hole portion 102 is formed in the first indented
12 portion 101, the negative lens formed therebetween has a weak focusing force in the vertical
13 direction while having a strong focusing force in the horizontal direction. Thus, the electron beam
14 passing through the negative lens is strongly focused in the horizontal direction so that the crossover
15 point corresponding to the point of an object of the electron beam is disposed near to the cathode.
16 A vertical component of the electron beam passing through the electron lens is weakly focused so
17 that the crossover point in the vertical direction is disposed far from the cathode 31. Thus, the
18 density of current of the electron beam emitted from the electron emission portion is higher in the
19 horizontal direction than in the vertical direction.

1 [0047] As described above, the electron beam passing through the negative lens passes through
2 a beam forming lens formed between the screen electrode 33 and the control electrode 32. The
3 electron beam in the horizontal direction which passes the negative lens is strongly focused because
4 an incident angle of the pre-focus lens increases, while the electron beam in the vertical direction is
5 weakly focused because the incident angle of the pre-focus lens decreases. In particular, when the
6 vertically elongated second electron beam passing hole 110 is formed at the screen electrode 33 or
7 the second electron beam passing hole 110 is formed of the first indented portion 111 and the second
8 electron beam passing hole portion 112, a focusing force in the horizontal direction can be
9 strengthened to some degree.

10 [0048] Since the point of an object in the horizontal direction of the electron beam is adjusted by
11 using the first indented portion and the first electron beam passing hole, a moiré phenomenon can
12 be minimized while a horizontal and vertical focus property of the electron beam can be improved.

13 [0049] FIG. 6 is an exploded perspective view showing an electron gun for a cathode ray tube, in
14 which the application of voltages is shown, in accordance with the principles of the present
15 invention. As shown in the drawing, the electron gun includes a cathode 51, a control electrode 52,
16 and a screen electrode 53 which form a triode portion, first, second, third, fourth, and fifth focusing
17 electrodes 54, 55, 56, 57, 58 which form an auxiliary lens and a focusing lens for focusing and
18 accelerating an electron beam, and a final acceleration electrode 59 installed adjacent to the fifth

focusing electrode 58 and forming a main lens.

[0050] The structures of the cathode 51 and the electron beam passing holes formed at the control electrode 52 and the screen electrode 53, forming the triode portion, are the same as those in the above-described preferred embodiments. That is, in the control electrode 52, the first electron beam passing hole 100 includes a first indented portion 101 formed at the output side surface of the control electrode 52 and the electron beam passing hole portion 102 formed at the first indented portion 101. The second electron beam passing hole 110 of the screen electrode 53 has a circular shape, a square shape having the same horizontal and vertical widths, or a vertically elongated rectangular shape.

[0051] Electron beam passing holes for forming auxiliary lenses including a quadrupole lens are formed at each of the first, second, third, fourth, and fifth focusing lenses 54, 55, 56, 57, and 58. In detail, circular electron beam passing holes 54H, 55H, and 56H are formed at the first and second focusing electrodes 54 and 55 and at the input side surface of the third focusing electrode 56, respectively. First and second vertically elongated electron beam passing holes 121 and 122 are formed at the output side surfaces of the third and fourth focusing electrodes 56 and 57, respectively. First and second horizontally elongated electron beam passing holes 131 and 132 are formed at the input side surfaces of the fourth and fifth focusing electrodes 57 and 58, respectively. The first and second vertically elongated electron beam passing holes 121 and 122 and the first and second horizontally elongated electron beam passing holes 131 and 132 may have a rectangular, oval, or

keyhole shape. However, the shape of the electron beam passing holes are not limited thereto and may be modified to have a variety of shapes, preferably in consideration of assembly of an electron gun.

[0052] Large diametric electron beam passing holes 58H and 59H through which three electron beams passes are formed at the output side surface of the fifth focus electrode 58 and the input side surface of the final acceleration electrode 59, forming the main lens, respectively. Three independent small diametric electron beam passing holes 58b and three independent small diametric electron beam passing holes 59a are formed at positions which is deeper than the large diametric electron beam passing holes 58H and 59H by a predetermined depth, respectively. Here, it is obvious that the independent small diametric electron beam passing holes can be modified into a variety of shapes according to the state of formation for the focus of an electron beam.

[0053] In the above preferred embodiment, the number of arrangement of the focusing electrodes for forming the auxiliary lens and main lens is not limited to the above preferred embodiment and a variety of modifications can be possible according to a property of a lens for focusing and diverging the electron beam.

[0054] In each of the electron guns having the above structures, a predetermined electric potential is applied to each of the electrodes. The relation of the application of a voltage is described as

1 follows.

2 **[0055]** A constant voltage VS is applied to the screen electrode 53 and the second focusing
3 electrode 55. A focusing voltage VF higher than the constant voltage VS is applied to the first and
4 fourth focusing electrodes 54 and 57. A dynamic focusing voltage VFD having the focusing voltage
5 VF as a base voltage and synchronized with the deflection yoke is applied to the third and fifth
6 focusing electrodes 56 and 58. An anode voltage VE which is higher than the focusing voltage VF
is applied to the final acceleration electrode 59. The state of application of the voltages can be varied
according to the state of formation of the electron lens by the electrodes forming the electron gun.

7
8
9
10
11 **[0056]** The operation of the electron gun for a color cathode ray tube having the above structure
according to the present invention is described with reference to FIG. 6.

12 **[0057]** When a predetermined voltage is applied to each of the electrodes forming the electron gun
13 50, a negative lens is formed between the control electrode 52 and the screen electrode 53. Since
14 the first electron beam passing hole 100 including the first indented portion 101 and the first electron
15 beam passing hole portion 102 is formed at the control electrode 52 and a circular or vertically
16 elongated electron beam passing hole is formed at the screen electrode 53 facing the control
17 electrode 52, the negative lens has a relatively weak focusing force in the vertical direction and a
relatively strong focusing force in the horizontal direction.

[0058] An auxiliary lens is formed between the first, second, and third focusing lenses 54, 55, and 56. First and second quadrupole lenses are formed between the third and fourth focusing lenses 56 and 57 and between the fourth and fifth focusing electrodes 57 and 58, respectively, according to the deflection of the electron beam. A main lens for finally-focusing and accelerating the electron beam is formed between the fifth focusing electrode 58 and the final acceleration electrode 59. The first and second quadrupole lenses can increase or decrease a difference between focusing and diverging forces in the vertical and horizontal directions by the vertically elongated electron beam passing hole and the horizontally elongated electron beam passing hole.

[0059] Thus, the electron beam emitted from the cathode 51 is focused and accelerated while passing through the electron lenses formed between the respective electrodes, deflected by the deflection yoke, and lands on the fluorescent film to excite fluorescent substance. In this process, while passing through the negative lens, the electron beam emitted from the cathode 51 receives a strong focusing force in the horizontal direction and relatively weak focusing force in the vertical direction, so that the profile of the electron beam has a vertically elongated shape. In particular, the crossover point of the electron beam in the vertical direction emitted from the cathode 51 is disposed far away from the cathode 51, whereas the crossover point of the electron beam in the horizontal direction is disposed near to the cathode 51 compared to the electron beam in the vertical direction.

1 [0060] As the electron beam in the vertical direction of the electron beam focused by the negative
2 lens passes through the pre-focus lens, an incident angle with respect to the pre-focus lens is
3 relatively reduced and the crossover point of the electron beam in the horizontal direction is disposed
4 near to the cathode 51, so that the incident angle of the electron beam in the horizontal direction with
5 respect to the pre-focus lens relatively increases.

6 [0061] When being deflected toward the periphery of the fluorescent film, the electron beam
7 passing through the pre-focus lens passes through the first and second quadrupole lenses formed as
8 the dynamic focus voltage is applied to the third and fourth focusing electrodes 56 and 57. Thus,
9 lowering of a focus property according to the focal distance according to a geometrical curvature of
10 a screen surface can be prevented.

11 [0062] As described above, in the electron gun for a color cathode ray tube according to the
12 present invention, by changing the shape of the electron beam passing holes of the control electrode
13 and the screen electrode forming the triode portion, the position of the crossover point which is an
14 imaginary point of an object of the electron beam so that distortion of the electron beam due to
15 irregular magnetic field of the deflection yoke can be minimized and dispersion of an image by the
16 electron beam landing on the fluorescent surface can be reduced. Also, by changing the position of
17 the crossover point of the electron beam in the horizontal direction and the vertical direction, a moiré
18 phenomenon at the low resolution can be reduced and simultaneously the resolution at the normal

current can be improved.

[0063] While the present invention has been illustrated by the description of embodiments thereof, and while the embodiments have been described in considerable detail, it is not the intention of the applicant to restrict or in any way limit the scope of the appended claims to such detail. Additional advantages and modifications will readily appear to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details, representative apparatus and method, and illustrative examples shown and described. Accordingly, departures may be made from such details without departing from the spirit or scope of the applicant's general inventive concept.